RUBBER ACRYLIC PAINT

White · 3.5 kg | Technical data & application

EN

A water-based acrylic-latex coating for interior and exterior surfaces. Suitable for wood, plywood, MDF, plaster, concrete, brick and appropriately prepared metal. Forms a washable coating for surfaces exposed to everyday wear and weather.

PRODUCT PARAMETERS

Colour / pack	**White / 3.5 kg**
Binder	**Acrylic latex**
Solids content	**56%**
Indicative coverage	**10 m²/kg**
Recommended coats	**2-3**
Drying at 23 °C and 50% RH	**Approximately 2 hours**
Application tools	**Brush, roller or spray**
Thinner	**Water**

PREPARATION AND APPLICATION

The surface must be clean and dry. Remove contamination, grease, salts and loose or corroded material. Prepare metal appropriately and abrade existing coatings where required for adhesion. Stir thoroughly before application. Apply 2-3 coats with a brush, roller or pneumatic spray.

For pneumatic spraying, dilute with 5-10% water to 20-22 seconds DIN 4 at 20 °C. Recommended nozzle: 1.4-1.5 mm; pressure: 3-4 bar.

STORAGE

Store tightly closed at +5 to +35 °C, protected from heat and direct sunlight. Shelf life: 2 years from manufacture.

SAFETY AND ENVIRONMENT

EUH208 Contains 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Wear water-resistant gloves. In case of eye contact, rinse immediately with plenty of water and seek medical attention. If swallowed, seek medical attention and show the packaging or label. Prevent release into drains, water and soil. Dispose of residues and packaging according to local requirements.